



NeoAgTech

INNOVATE | GROW | SUSTAIN

Material Handling Excellence

Manufactured with
Design Expertise from Europe



Agriculture



Industry



Infrastructure



Dairy



Municipalities



Defence



NeoAgTech

INNOVATE | GROW | SUSTAIN

AT2400

Built to Reach Higher



GOVT. SUBSIDY ELIGIBLE



MAXIMUM PERFORMANCE

High lift capacity for every-duty task.



BUILT TO LAST

Strong, durable & reliable in every condition.



VERSATILE ATTACHMENT

Multiple attachment options for every application.



OPERATOR COMFORT

Smooth product for better productivity and safety.

**POWERING PRODUCTIVITY.
DELIVERING RESULTS.**



Bale Handling



Material Handling



Loading & Unloading



Agricultural Solutions

AT2400 – SPECIFICATIONS

Specification	Dimension (Foot)	Dimension (mm)
Normal Reach at Ground	11' 8"	3556
Telescopic Reach at Ground	17'	5182
Roll-Rank Angle	43 Degree	-
Dump Angle	43 Degree	-
Normal Dump Height	13' 8"	4166
Normal Load-over Height	16'	4877
Loader Hinge Pin Height (Normal)	17'	5182
Telescopic Dump Height	20' 11"	6375
Telescopic Loader Height	22'	6706
Loader Hinge Pin Height (Telescope)	22'	6706

MULTIPLE ATTACHMENTS. MAXIMUM VERSATILITY.



Bale Spear



Grapple Bucket



Forklift Bucket



Standard Bucket



NeoAgTech

INNOVATE | GROW | SUSTAIN

AT1200 Pro

More Reach.
More Productivity.

A versatile high-performance loader designed for bale handling, material movement and everyday agricultural operations.



MAXIMUM PERFORMANCE

High Lift Capacity
Faster Loading
Superior Reach



BUILT TO LAST

Heavy-Duty Structure
Rugged Reliability
Proven Durability



VERSATILE ATTACHMENTS

Multiple Attachments
for Every Application



OPERATOR COMFORT

Smooth Operation
Better Visibility
Enhanced Productivity



GOVT. SUBSIDY ELIGIBLE



APPLICATIONS



Bale Handling



Material Handling



Loading & Unloading



Agricultural Solutions

AT1200 Pro – SPECIFICATIONS

NeoAgtech AT 1200 Pro Specifications

Specification	Dimension (Foot)	Dimension (mm)
Reach at Ground	8'.4"	2590 mm
Roll-back Angle	45 Degree	45 Degree
Dump Angle	45 Degree	45 Degree
Dump Height	13'.8"	4164 mm
Load-over Height	16'.6"	5030 mm
Loader Hinge Pin Height	13'.0"	3962 mm

MULTIPLE ATTACHMENTS, MORE PRODUCTIVITY



Bale Grabber



Grapple Bucket



Forklift Bucket



Standard Bucket



NeoAgTech

INNOVATE | GROW | SUSTAIN

AT1200

DETACHABLE LOADER

Compact Fit. Powerful Lift.

Engineered for Lower HP Tractors.

Built for Maximum Utility.

A detachable loader designed for lower HP tractors, delivering powerful performance for material handling, lifting and everyday tasks on farms and in industry.

 **Compatible with Lower HP Tractors**
More tractors. More versatility.

 **Detachable Design**
Quick attach & detach.
Work the way you need.

 **Built for Performance**
Compact in size.
Powerful in every lift.



ROBUST CONSTRUCTION
Built tough for long lasting durability and reliable performance.



HIGH LIFT PERFORMANCE
Excellent lift height and reach for higher productivity.



MULTIPLE ATTACHMENTS
One loader. Many attachments. Unlimited possibilities.



OPERATOR FRIENDLY
Easy to operate, comfortable and more productive.



FARM & INDUSTRY READY
Perfect for agriculture, construction, material handling and industrial applications.



GOVT. SUBSIDY ELIGIBLE



APPLICATIONS



Bale Handling



Material Handling



Loading & Unloading



Agricultural Solutions

AT1200 - SPECIFICATIONS

NeoAgtech AT 1200 Specifications

Specification	Dimension (Foot)	Dimension (mm)
Reach at Ground	4'.6"	1341 mm
Roll-back Angle	45 Degree	45 Degree
Dump Angle	45 Degree	45 Degree
Dump Height	10'.6"	3200 mm
Load-over Height	12'.6"	3810 mm
Loader Hinge Pin Height	11'.6"	3505 mm

MULTIPLE ATTACHMENTS, MULTIPLE OPERATIONS



Bale Spear



Bale Grabber



Forklift Bucket



Standard Bucket



NeoAgTech

— INNOVATE | GROW | SUSTAIN —

NeoAgTech Machines Pvt. Ltd.



Hisar Road - Sirsa 125055, Haryana (INDIA)

+91 75021 21100

neoagtechmachines@gmail.com

www.neoagtechmachines.com